In the Claims:

5

10

20

Amend the claims as follows:

1. (Currently amended) A method for sending messages over secure communication links in networks, comprising: providing at least a first terminal in communication with being able to change its method of network access and at least one other a second terminal with one or more possible intermediate computers between the first terminal and the other terminal performing network address and/or other translations,

establishing a first secure communication link being
cotablished between an initial network address of the first terminal and the a network address of the other second terminal,

the link defining at least the addresses of the two terminals, and the first terminal performing encapsulation of messages sent in the first in said secure communication link using a

first encapsulation method, to overcome network address and/or other translations made by said intermediate computers on the route, comprising:

 $\frac{a}{a}$ the first terminal moving from $\frac{a}{a}$ the initial network address to a new network address,

b) the first terminal sending an encapsulated request message, using the first encapsulation method, from the first terminal to the other second terminal to change communication between the first terminal and the second terminal from the first

secure communication link to a second secure communication

link extending said secure connection to be between the new

network address of the first terminal and the network address
of the second other terminal, the encapsulated request message

also containing a description of the first encapsulation

35 method performed by the first terminal,

RF Attorney Docket No. 290.1075USN 8/20/07 - 3 -

5

25

the second terminal receiving the encapsulated request message,

the second terminal using the description of the first encapsulation method to on the basis of which description the other terminal detects translations of the encapsulated request message performed by said intermediate computers disposed en route between the first terminal and the second terminal,

c) the other second terminal responding to the first terminal with a reply message, the reply message having with a description about detected translations made by said possible intermediate computers disposed between the new network address of the first terminal and the other network address of the second terminal and/or encapsulation methods supported by the other second terminal,

the first terminal receiving the reply message and the description about translation made by intermediate computers and encapsulation methods supported by the second terminal, the first terminal selecting an encapsulation method to

encapsulate a message based on the description of the reply message, and

d) thereafter the first terminal sending the encapsulated message from the first terminal to the other second terminal

by using the information sent with said reply.

2. (Currently amended) The method of claim 1 wherein the method further comprises the second terminal detecting address translations performed by the intermediate computers and including a description of translated source and/or

destination addresses in description of the reply message include source and/or destination addresses on the basis of which the second receiving terminal detects address translations performed by intermediate computers.

35 3. (Currently amended) The method of claim 1 wherein the

RF Attorney Docket No. 290.1075USN 8/20/07 - 4 -

description of the reply message has of the message includes information about encapsulation protocols, as well as source and destination transmission control protocol (TCP) or user datagram protocol (UDP) ports.

5

4. (Currently amended) The method of claim 3 wherein the method further comprises performing network address translation (NAT) traversal is performed by UDP encapsulation or TCP encapsulation and/or by another encapsulation.

10

- 5. (Currently amended) The method of claim 1 wherein after receiving of the request message by said other terminal sent in step c), the other terminal determines by the method further comprises the second terminal examining the
- encapsulated request message to determine, which translations and/cr encapsulations are required in the traffic between the first terminal and the other second terminal.
- 6. (Currently amended) The method of claim 5 wherein the reply
 20 message of step c) contains information about the second
 secure communication link to be used between the new network
 address of the first terminal and said other the second
 terminal.
- 7. (Currently amended) The method of claim 6 wherein the information about the second secure communication link includes information about whether network address translation (NAT) traversal is and/or other encapsulation should be used.
- 30 8. (Currently amended) The method of claim 1 wherein the method further comprises in step c) the first terminal compares comparing the descriptions of the request message with the description of the respective reply messages and sends sending all subsequent messages from this the new network address based on the comparison of the descriptions

regarding which on the basis of the comparison telling what encapsulations, protocols and rules to use should be used in the further communication.

- 9. (Currently amended) The method of claim 1 wherein the <u>first</u> secure communication link is formed by using <u>an the Internet</u> security protocol IPSec <u>protocol</u>.
- 10. (Currently amended) The method of claim 9 wherein the

 reply message in step d) is sent by using IPSec and a network

 address translation (NAT) traversal that is updated to the new

 network address of the first terminal.
- 11. (Currently amended) The method of claim 1 wherein the

 reply message in step-d) is sent without a network address

 translation (NAT) traversal in the first secure communication
 link when the description of the reply message corresponds to
 the description of the request message the descriptions

 correspond to each other.
 - 12. (Currently amended) The method of claim 1 wherein the method further comprises providing a the secure connection with is an Internet security protocol (IPSec) security association (SA).
 - 13. (Currently amended) The method of claim 12 wherein the method further comprises using a key exchange mechanism that passes through a network address translation (NAT) is used when forming the IPSec SA.
 - 14. (Currently amended) The method of claim 12 wherein the a key exchange mechanism protocol is an Internet key exchange (IKE) when the a network address translation (NAT) device supports the a user datagram protocol (UDP) protocol.

30

20

25

- RF Attorney Docket No. 290.1075USN 8/20/07 6 -
- 15. (Currently amended) The method of claim 14 wherein a the key exchange mechanism is used when forming the IPSec SA and wherein several traversal mechanisms are used simultaneously to increase the a chance that at least one of the traversal mechanisms passes them pass through the NAT device.
- 16. (Previously presented) The method of claim 12 wherein a key exchange mechanism is performed when forming the IPSec SA in which a negotiation process is used to agree on protocols to be used in the further communication.
 - 17. (Currently amended) The method of claim 12 wherein an encapsulation protocol is used in $\frac{1}{2}$ key exchange mechanism when forming the IPSec SA.
- 18. (Currently amended) The method of claim 1 wherein the network address of the other second terminal is the an end destination address of messages sent from the first terminal in which and using case transport or tunnel mode is used in the first and second secure IPSec communication links.
 - 19. (Currently amended) The method of claim 1 wherein <u>a</u> the destination address of the message is the <u>a</u> network address of a host which is not the other second terminal, in which case and using tunnel mode or transport mode together with a tunneling protocol is used in the IPSee the first and second secure communication links.
- 20. (Currently amended) The method of claim 1 wherein several request messages of step b) are sent, each request message being processed using a different traversal mechanism, where after the other terminal indicates and the second terminal indicating in the reply message which encapsulation methods is to be used in the further-communication.

5

10

15

20

25